



EuroConsult Dimitrios Piretzidis | Mörikestraße 9 | D - 71522 Backnang

Datasheet

Prod. no. RE 007

Date 26.04.2024

COMAC Dust Control System Akkua Jet 65S



TECHNICAL SPECIFICATIONS

Manufacturer: COMAC

Description: Dust Control system / fogulizer

Type: Akkua Jet 65S

Version: with 5 m articulated arm

Year of construction: 2012

Range: approx. 65 m (significantly more in wind direction)

Rotation: 0-360° (hydraulic)

Vertical adjustment: -15°/+50° (hydraulic)

Area coverage (theoretical): approx. 13,300 sqm

Water consumption: from 1,500 to approx. 8,000 L/h

Number of nozzle rings: 3 pcs. (separately switchable)

Number of nozzles per ring: 52 pcs.

Number of nozzles in total: 156 pcs.

Fan power: 11.5 kW

Water pump power: 4 kW

Water filter: at 100 µm (stainless steel filter)

Operating water pressure: approx. 15 - 22 bar

Electrical connection: 400V/32A CE

Control voltage: 24 V

Water connection: 1". IG

Average air speed: approx. 38 m/s

Air flow rate: approx. 30,000 cbm/h

Protection class of machine: IP55

Total weight: approx. 1,100 kg

SPECIFIC COMMENT

- Good technical condition
- Generator: MOSA, Type GE 35 PSX-EAS, Output: 33 kVA / 26.4 kW
- Ideal for dust or odour control in recycling, demolition, etc.

If you are interested, we would be happy to send you a detailed offer with photo documentation.

Yours sincerely,

EuroConsult Dimitrios Piretzidis